

```

1 #include <iostream>
2
3 template<typename T> void p(T x) { std::cout << x; }
4
5 class A { };
6 class B : public A { };
7 class C : public A { };
8
9 void foo() {
10     p("1");
11     throw C();
12 }
13
14 int main() {
15     try {
16         p("2");
17         foo();
18         p("3");
19     } catch(B) {
20         p("4");
21     } catch(C) {
22         p("5");
23     } catch(A) {
24         p("6");
25     }
26     p("7");
27 }

```

What might happen if you try to compile this code?

```
1 #include <iostream>
2
3 template<typename T> void p(T x) { std::cout << x; }
4
5 class A {
6 protected:
7     void foo() { p("foo"); };
8 };
9
10 class B : virtual public A {
11 public:
12     void bar() { p("bar"); };
13 };
14
15 int main() {
16     B b;
17     b.foo();
18 }
```

what might happen if you try to compile, link and run this program?

```
1 #include <iostream>
2
3 template<typename T> void p(T x) { std::cout << x; }
4
5 class A {
6 public:
7     virtual void boo() { p("A"); };
8 };
9
10 class B : public A {
11 public:
12     virtual void boo() { p("B"); };
13 };
14
15 int main() {
16     try {
17         throw B();
18     } catch( A a ) {
19         a.boo();
20     }
21 }
```

what might happen if you try to compile, link and run this program?

```

1 #include <iostream>
2
3 template<typename T> void p(T x) { std::cout << x; }
4
5 class A { };
6
7 int main() {
8     p("0");
9     try {
10         p("1");
11         try {
12             p("2");
13             throw A();
14             p("3");
15         } catch(...) {
16             p("4");
17             throw;
18             p("5");
19         }
20     } catch(A a) {
21         p("6");
22         throw;
23         p("7");
24     }
25     p("8");
26 }

```

what might happen if you try to compile, link and run this program?

```

1 #include <iostream>
2
3 template<typename T> void p(T x) { std::cout << x; }
4
5 class B {
6 public:
7     B() { p("B"); }
8     ~B() { p("b"); }
9 };
10
11 class A {
12     B * v;
13 public:
14     A() { p("A"); v = new B[3]; throw "x"; }
15     ~A() { p("a"); delete[] v; }
16 };
17
18 int main() {
19     try {
20         p("0");
21         A a;
22         p("1");
23     } catch( const char * s ) {
24         p(s);
25     }
26 }

```

what might happen if you try to compile, link and run this program?

```

1 #include <iostream>
2
3 template<typename T> void p(T x) { std::cout << x; }
4
5 class B {
6 public:
7     B() { p("B"); throw "x"; }
8     ~B() { p("b"); }
9 };
10
11 class A {
12     B b;
13 public:
14     A() try : b() { p("A"); } catch(...) { p("y"); }
15     ~A() { p("a"); }
16 };
17
18 int main() {
19     try {
20         p("0");
21         A a;
22         p("1");
23     } catch( const char * s ) {
24         p(s);
25     }
26 }

```

what might happen if you try to compile, link and run this program?

```
1 #include <iostream>
2
3 template<typename T> void p(T x) { std::cout << x; }
4
5 void foo() throw() {
6     throw "x";
7 };
8
9 int main() {
10     try {
11         p("0");
12         foo();
13         p("1");
14     } catch( const char * s ) {
15         p(s);
16     }
17 }
```

what might happen if you try to compile, link and run this program?

```
1 #include <iostream>
2
3 template<typename T> void p(T x) { std::cout << x; }
4
5 struct B {
6     void foo(int) { p(1); }
7 };
8
9 struct C : B {
10     void foo(float) { p(2); }
11 };
12
13 int main() {
14     C c;
15     c.foo(42);
16 }
```

what might happen if you try to compile, link and run this program?


```
1 #include <iostream>
2
3 template<typename T> void p(T x) { std::cout << x; }
4
5 struct A {
6     A() { p('A'); }
7 };
8
9 struct B : A {
10     B() { p('B'); }
11 };
12
13 struct C : virtual A {
14     C() { p('C'); }
15 };
16
17 struct D : B, C {
18     D() { p('D'); }
19 };
20
21 int main() {
22     D d;
23 }
```

what might happen if you try to compile, link and run this program?

```

1 #include <iostream>
2 #include <typeinfo>
3
4 template<typename T> void p(T x) { std::cout << x; }
5
6 struct A {
7     virtual void foo() { p("A"); }
8 };
9
10 struct B : A {
11     virtual void foo() { p("B"); }
12 };
13
14 struct C : A {
15     virtual void foo() { p("C"); }
16 };
17
18 int main() {
19     A * b = new B;
20     A * c = new C;
21     b = c;
22     b->foo();
23     b = dynamic_cast<B*>(c);
24     b->foo();
25 }

```

what might happen if you try to compile, link and run this program?

```
1 #include <iostream>
2 #include <typeinfo>
3
4 struct Foo {
5 };
6
7 struct Bar : Foo {
8 };
9
10 struct Gaz : Foo {
11 };
12
13 int main() {
14     Foo * b = new Bar;
15     Foo * c = new Gaz;
16     std::cout << typeid(*b).name();
17     std::cout << typeid(*c).name();
18 }
```

what might happen if you try to compile, link and run this program?